according to UK REACH Regulation

# **Better Feet Prep & Finish**

Revision date: 22.05.2024 Product code: 603 Page 1 of 15

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Cleaner

#### Further trade names

30001.30002

Product group: Zulieferprodukt

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Cosmetics, personal care products

# 1.3. Details of the supplier of the safety data sheet

Company name: CosTrade Beauty Consulting GmbH

Street: Buxera 25
Place: AT-6837 Weiler

 Telephone:
 +43 5523 53750 16
 Telefax: +43 5523 53750 4

 Contact person:
 Dipl.-Chem. Katrin Kaltenberg
 Telephone: +49 6723 6020 761

E-mail: katrin.kaltenberg@wilde-group.com

Internet: www.costrade.at

1.4. Emergency telephone +49 6723 6020 761 This telephone number is available during office hours only.

number:

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

## **GB CLP Regulation**

Flam. Liq. 2; H225 Eye Dam. 1; H318 STOT SE 3: H336

Full text of hazard statements: see SECTION 16.

The Product is subject to the German Cosmetics Ordinance.

# 2.2. Label elements

#### **GB CLP Regulation**

# Hazard components for labelling

propan-1-ol; n-propanol butanone; ethyl methyl ketone ethyl acetate

Signal word: Danger

Pictograms:







#### **Hazard statements**

H225 Highly flammable liquid and vapour.
 H318 Causes serious eye damage.
 H336 May cause drowsiness or dizziness.

# **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

according to UK REACH Regulation

	Better Feet Prep & Finish	
Revision date: 22.05.2024	Product code: 603	Page 2 of 15

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P370+P378 In case of fire: Use sand, extinguishing powder or alcohol-resistant foam to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

#### Special labelling of certain mixtures

EUH208 Contains citral. May produce an allergic reaction.

#### 2.3. Other hazards

P310

Keep out of the reach of children.

Irritating to eyes, respiratory system and skin. May cause sensitization by skin contact. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. When using, do not eat, drink or smoke. Wash hands before breaks and at the end of workday. Repeated absorption may cause disorder of central nervous system. liver, kidneys and blood.

# **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

#### Chemical characterization

Cosmetics, personal care products: Contains organic solvents.

#### Relevant ingredients

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	Classification (GB CLP Regulatio	n)			
71-23-8	3-8 propan-1-ol; n-propanol				
	200-746-9	603-003-00-0			
	Flam. Liq. 2, Eye Dam. 1, STOT SE 3; H225 H318 H336				
78-93-3	butanone; ethyl methyl ketone				
	201-159-0	606-002-00-3			
	Flam. Liq. 2, Eye Irrit. 2, STOT SI	3; H225 H319 H336 EUH066			
141-78-6	ethyl acetate			5 - < 10 %	
	205-500-4	607-022-00-5			
	Flam. Liq. 2, Eye Irrit. 2, STOT SI	3; H225 H319 H336 EUH066			
5392-40-5	citral				
	226-394-6	605-019-00-3			
	Skin Irrit. 2, Skin Sens. 1; H315 H317				

Full text of H and EUH statements: see section 16.

# Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity			
	Specific Conc. Limits, M-factors and ATE					
78-93-3	201-159-0	butanone; ethyl methyl ketone	20 - < 25 %			
	oral: LD50 = 2054 mg/kg					
141-78-6	205-500-4	ethyl acetate	5 - < 10 %			
	inhalation: LC50 = >29 mg/l (vapours); dermal: LD50 = >20000 mg/kg; oral: LD50 = 4934 mg/kg					
5392-40-5	226-394-6	citral	< 1 %			
	dermal: LD50	= >2000 mg/kg; oral: LD50 = 6800 mg/kg				

#### **Further Information**

The Product is subject to the German Cosmetics Ordinance.

according to UK REACH Regulation

# **Better Feet Prep & Finish**

Revision date: 22.05.2024 Product code: 603 Page 3 of 15

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

Remove from exposure, lie down. Take off all contaminated clothing immediately. First aider needs to protect himself.

#### After inhalation

Move to fresh air. Keep patient warm and at rest. In case of shortness of breath, give oxygen. If breathing has stopped, apply artificial respiration. If unconscious place in recovery position and seek medical advice.

#### After contact with skin

Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.

#### After contact with eyes

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult a physician.

#### After ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Consult a physician. If unconscious place in recovery position and seek medical advice. Never give anything by mouth to an unconscious person.

### 4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause irritation to the eyes, respiratory system and the skin. May cause sensitization by skin contact. Vapours may cause drowsiness and dizziness. Symptoms: Exposure may result in reddening, tears and itching of the eyes and soreness in the nose and throat, together with coughing. Difficulty in breathing. May cause headache and dizziness. Unconsciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

### Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

#### 5.2. Special hazards arising from the substance or mixture

Vapours are heavier than air and may spread along floors. Vapors may spread long distances and ignite. Vapours may form explosive mixtures with air. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from sources of ignition - No smoking. Use water spray to cool unopened containers. Container may rupture on heating.

Hazardous combustion products: Carbon monoxide, Carbon dioxide (CO2)

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit. Use only explosion-proof equipment.

#### Additional information

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Prevent fire extinguishing water from contaminating surface water or the ground water system. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

# **SECTION 6: Accidental release measures**

Print date: 22.05.2024

# **Safety Data Sheet**

according to UK REACH Regulation

# **Better Feet Prep & Finish**

Revision date: 22.05.2024 Product code: 603 Page 4 of 15

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Wear personal protective equipment. Keep people away from and upwind of spill/leak. Keep away from heat and sources of ignition. Avoid contact with the skin and the eyes. S23 - Do not breathe qas/fumes/vapour/spray.

#### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3. Methods and material for containment and cleaning up

#### Other information

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Ensure adequate ventilation. Use explosion-proof equipment. Clean contaminated surface thoroughly.

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep containers tightly closed in a dry, cool and well-ventilated place. Ensure adequate ventilation, especially in confined areas. Vapours are heavier than air and may spread along floors. Avoid contact with skin, eyes and clothing. Ensure that eyewash stations and safety showers are close to the workstation location. Eye wash bottle with pure water.

#### Advice on protection against fire and explosion

Combustible Liquid. Vapors may spread long distances and ignite. Take measures to prevent the build up of electrostatic charge. Use only explosion-proof equipment. Use only in an area containing explosion proof equipment. Keep away from sources of ignition - No smoking.

### Advice on general occupational hygiene

Take off all contaminated clothing immediately. Avoid contact with the skin and the eyes.

Ensure adequate ventilation, especially in confined areas. Avoid breathing vapors, mist or gas.

When using, do not eat, drink or smoke. Wash hands before breaks and at the end of workday.

#### Further information on handling

Handle in accordance with good industrial hygiene and safety practice. When using, do not eat, drink or smoke.

# 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep in an area equipped with solvent resistant flooring. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Store in original container. Keep away from direct sunlight.

#### Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Materials to avoid: Oxidizing and spontaneously flammable products, Flammable materials, Organic peroxides, Oxidizing agents

### 7.3. Specific end use(s)

Cosmetic product

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

according to UK REACH Regulation

# Better Feet Prep & Finish

Revision date: 22.05.2024 Product code: 603 Page 5 of 15

# **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	734		TWA (8 h)	WEL
		400	1468		STEL (15 min)	WEL
71-23-8	Propan-1-ol	200	500		TWA (8 h)	WEL
		250	625		STEL (15 min)	WEL

# **Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

according to UK REACH Regulation

# **Better Feet Prep & Finish**

Revision date: 22.05.2024 Product code: 603 Page 6 of 15

# **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
71-23-8	propan-1-ol; n-propanol	,	,	
Worker DNEL,	long-term	inhalation	systemic	268 mg/m³
Worker DNEL,	acute	inhalation	systemic	1723 mg/m³
Worker DNEL,	long-term	dermal	systemic	136 mg/kg bw/day
Consumer DNE	EL, long-term	inhalation	systemic	80 mg/m³
Consumer DNE	EL, acute	inhalation	systemic	1036 mg/m³
Consumer DNE	EL, long-term	dermal	systemic	81 mg/kg bw/day
Consumer DNE	EL, long-term	oral	systemic	61 mg/kg bw/day
78-93-3	butanone; ethyl methyl ketone		•	
Worker DNEL,	long-term	inhalation	systemic	600 mg/m³
Worker DNEL,	long-term	dermal	systemic	1161 mg/kg bw/day
Consumer DNE	EL, long-term	inhalation	systemic	106 mg/m³
Consumer DNE	EL, long-term	dermal	systemic	412 mg/kg bw/day
Consumer DNE	EL, long-term	oral	systemic	31 mg/kg bw/day
141-78-6	ethyl acetate			
Worker DNEL,	long-term	inhalation	systemic	734 mg/m³
Worker DNEL,	acute	inhalation	systemic	1468 mg/m³
Worker DNEL,	long-term	inhalation	local	734 mg/m³
Worker DNEL,	acute	inhalation	local	1468 mg/m³
Worker DNEL,	long-term	dermal	systemic	63 mg/kg bw/day
Consumer DNE	EL, long-term	inhalation	systemic	367 mg/m³
Consumer DNE	EL, acute	inhalation	systemic	734 mg/m³
Consumer DNE	EL, long-term	inhalation	local	367 mg/m³
Consumer DNE	EL, acute	inhalation	local	734 mg/m³
Consumer DNE	EL, long-term	dermal	systemic	37 mg/kg bw/day
Consumer DNE	EL, long-term	oral	systemic	4,5 mg/kg bw/day
5392-40-5	citral			
Worker DNEL,	long-term	inhalation	systemic	9 mg/m³
Worker DNEL,	long-term	dermal	systemic	1,7 mg/kg bw/day
Worker DNEL,	long-term	dermal	local	0,14 mg/cm <sup>2</sup>
Consumer DNE	EL, long-term	inhalation	systemic	2,7 mg/m³
Consumer DNE	EL, long-term	dermal	systemic	1 mg/kg bw/day
Consumer DNE	EL, long-term	dermal	local	0,14 mg/cm <sup>2</sup>
Consumer DNE	EL, long-term	oral	systemic	0,6 mg/kg bw/day

according to UK REACH Regulation

# **Better Feet Prep & Finish**

Revision date: 22.05.2024 Product code: 603 Page 7 of 15

# **PNEC values**

CAS No	Substance	
Environment	tal compartment	Value
71-23-8	propan-1-ol; n-propanol	<u> </u>
Freshwater		6,83 mg/l
Freshwater (	(intermittent releases)	10 mg/l
Marine wate	г	0,683 mg/l
Freshwater s	sediment	27,5 mg/kg
Marine sedir	ment	2,75 mg/kg
Soil		1,49 mg/kg
78-93-3	butanone; ethyl methyl ketone	
Freshwater		55,8 mg/l
Freshwater (	(intermittent releases)	55,8 mg/l
Marine wate	r	55,8 mg/l
Freshwater s	sediment	284,74 mg/kg
Marine sedir	ment	284,7 mg/kg
Secondary p	1000 mg/kg	
Micro-organisms in sewage treatment plants (STP)		709 mg/l
Soil		22,5 mg/kg
141-78-6	ethyl acetate	
Freshwater		0,24 mg/l
Freshwater (	(intermittent releases)	1,65 mg/l
Marine wate	r	0,024 mg/l
Freshwater s	sediment	1,15 mg/kg
Marine sedir	ment	0,115 mg/kg
Secondary p	poisoning	200 mg/kg
Micro-organi	isms in sewage treatment plants (STP)	650 mg/l
Soil		0,148 mg/kg
5392-40-5	citral	
Freshwater		0,00678 mg/l
Freshwater (	(intermittent releases)	0,0678 mg/l
Marine wate	r	0,000678 mg/l
Freshwater s	sediment	0,125 mg/kg
Marine sedin	ment	0,0125 mg/kg
Micro-organi	isms in sewage treatment plants (STP)	1,6 mg/l
Soil		0,029 mg/kg

# 8.2. Exposure controls













# Appropriate engineering controls

Information about special precautions needed for bulk handling is available on request. Handle in accordance with good industrial hygiene and safety practice. To avoid risks to man and the environment, comply with the

according to UK REACH Regulation

# **Better Feet Prep & Finish**

Revision date: 22.05.2024 Product code: 603 Page 8 of 15

instructions for use.

#### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Tightly fitting safety goggles

#### Hand protection

Use protective skin cream before handling the product.

Solvent-resistant gloves (butyl-rubber)

Break through time: >= 1 h Glove thickness: 0,5 mm

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Replace when worn.

#### Skin protection

impervious clothing

### Respiratory protection

Use only with adequate ventilation. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection complying with EN 141. Recommended Filter type: A

#### **Environmental exposure controls**

The product should not be allowed to enter drains, water courses or the soil. Inform the responsible authorities in case of gas leakage, or of entry into waterways, soil or drains.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: colourless
Odour: characteristic

Melting point/freezing point:

No further relevant information

available.

Boiling point or initial boiling point and 77 °C

boiling range:

Flammability: No further relevant information available. Lower explosion limits: 1,5 vol. % Upper explosion limits: 13,5 vol. % Flash point: -9 °C Auto-ignition temperature: 385 °C

Decomposition temperature: No further relevant information available.

pH-Value: No further relevant information

available.

Viscosity / kinematic:

No further relevant information available.

Water solubility:

No further relevant information available.

(at 20 °C)

Dissolution rate:

Partition coefficient n-octanol/water:

Dispersion stability:

No further relevant information available.

No further relevant information available.

No further relevant information available.

Vapour pressure: 101 hPa

(at 20 °C)

Vapour pressure:

Density (at 20 °C):

No further relevant information available.

0,81 g/cm³

### 9.2. Other information

# Other safety characteristics

Solvent content: 99,80 %

according to UK REACH Regulation

# **Better Feet Prep & Finish**

Revision date: 22.05.2024 Product code: 603 Page 9 of 15

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No data is available on the product itself.

# 10.2. Chemical stability

Keep containers tightly closed in a cool, well-ventilated place.

#### 10.3. Possibility of hazardous reactions

Vapours may form explosive mixtures with air.

#### 10.4. Conditions to avoid

Keep away from direct sunlight. Keep away from heat and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. Do not expose to temperatures above 40 °C.

#### 10.5. Incompatible materials

Oxidizing agents, Alkali metals, Alkaline earth metals

#### 10.6. Hazardous decomposition products

acetic acid. In case of fire hazardous decomposition products may be produced such as: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke. Oxidizing and spontaneously flammable products.

# **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Toxicocinetics, metabolism and distribution

No data is available on the product itself.

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) 25543 mg/l

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
78-93-3	butanone; ethyl methyl k	etone				
	oral	LD50 mg/kg	2054	Rat		OECD 423
141-78-6	ethyl acetate					
	oral	LD50 mg/kg	4934	Rabbit		OECD 401
	dermal	LD50 mg/kg	>20000	Rat		
	inhalation (4 h) vapour	LC50	>29 mg/l	Rat		
5392-40-5	citral					
	oral	LD50 mg/kg	6800	rat		
	dermal	LD50 mg/kg	>2000	rat		

### Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye damage.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Print date: 22.05.2024

# **Safety Data Sheet**

according to UK REACH Regulation

# **Better Feet Prep & Finish**

Revision date: 22.05.2024 Product code: 603 Page 10 of 15

#### Sensitising effects

Based on available data, the classification criteria are not met.

Contains citral. May produce an allergic reaction.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (propan-1-ol; n-propanol; butanone; ethyl methyl ketone)

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

# Specific effects in experiment on an animal

No data is available on the product itself.

#### 11.2. Information on other hazards

#### Other information

Health injuries are not known or expected under normal use.

#### Further information

Harmful if swallowed. Effects due to ingestion may include: Nausea, narcosis, Weakness, Dizziness, Unconsciousness. If inhaled: Irritation of mucous membranes, Dizziness. Repeated exposure may cause skin dryness or cracking.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

No data is available on the product itself.

according to UK REACH Regulation

# **Better Feet Prep & Finish**

Revision date: 22.05.2024 Product code: 603 Page 11 of 15

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
78-93-3	butanone; ethyl methyl ketone							
	Acute fish toxicity	LC50 mg/l	2993	96 h	Pimephales promelas (fathead minnow)		OECD 203	
	Acute algae toxicity	ErC50 mg/l	2029	96 h	Pseudokirchneriella subcapitata		OECD 201	
	Acute crustacea toxicity	EC50	308 mg/l	48 h	Daphnia magna (Big water flea)		OECD 202	
	Fish toxicity	NOEC mg/l	1170	4 d	Pimephales promelas (fathead minnow)		OECD 203	
	Crustacea toxicity	NOEC	68 mg/l	2 d	Daphnia magna (Big water flea)		OECD 202	
	Acute bacteria toxicity	EC50 mg/l ( )	1150		Pseudomonas putida		DIN 38412 / part 8	
141-78-6	ethyl acetate							
	Acute fish toxicity	LC50	220 mg/l	96 h	Pimephales promelas (fathead minnow)			
	Acute algae toxicity	ErC50 mg/l	5600	72 h	Desmodesmus subspicatus		OECD 201	
	Acute crustacea toxicity	EC50	165 mg/l	48 h	Daphnia			
	Fish toxicity	NOEC mg/l	9,65	32 d	Pimephales promelas (fathead minnow)		OECD 210	
	Algae toxicity	NOEC mg/l	1000	3 d	Desmodesmus subspicatus		OECD 201	
	Crustacea toxicity	NOEC	2,4 mg/l	21 d	Daphnia magna (Big water flea)		OECD 211	
5392-40-5	citral							
	Acute fish toxicity	LC50 mg/l	6,78	96 h	Leuciscus idus (golden orfe)		DIN 38412	
	Acute algae toxicity	ErC50 mg/l	103,84	72 h	Desmodesmus subspicatus		DIN 38412 / part 9	
	Acute crustacea toxicity	EC50	6,8 mg/l	48 h	Daphnia magna (Water flea)			
	Fish toxicity	NOEC	4,6 mg/l	4 d	Leuciscus idus (golden orfe)		DIN 38412	
	Acute bacteria toxicity	EC50	160 mg/l	0,5 h	Respiration inhibition of activated sludge		OECD 209	

# 12.2. Persistence and degradability

No data is available on the product itself.

according to UK REACH Regulation

# **Better Feet Prep & Finish**

Revision date: 22.05.2024 Product code: 603 Page 12 of 15

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation	•		•		
78-93-3	butanone; ethyl methyl ketone					
	OECD 301D/ EEC 92/69/V, C.4-E	98%	28			
	Readily biodegradable.					
141-78-6	ethyl acetate					
		62%	10			
	Readily biodegradable.	-	-			
5392-40-5	citral					
	Degradation OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D	>90%	28			
	Readily biodegradable.		•			

#### 12.3. Bioaccumulative potential

No data is available on the product itself.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
78-93-3	butanone; ethyl methyl ketone	0,3
141-78-6	ethyl acetate	0.68 - 0.73
5392-40-5	citral	2,76

### **BCF**

CAS No	Chemical name	BCF	Species	Source
5392-40-5	citral	89,72		

#### 12.4. Mobility in soil

No data is available on the product itself.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

This preparation contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This preparation contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

# 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No data is available on the product itself.

#### **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

# **Disposal recommendations**

Dispose of contents/container in accordance with local regulation.

# List of Wastes Code - residues/unused products

200113 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately

collected fractions (except 15 01); Solvents; hazardous waste

# List of Wastes Code - contaminated packaging

200113 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND

INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately

collected fractions (except 15 01); Solvents; hazardous waste

according to UK REACH Regulation

# **Better Feet Prep & Finish**

Revision date: 22.05.2024 Product code: 603 Page 13 of 15

### Contaminated packaging

Dispose of contents/container in accordance with local regulation.

# **SECTION 14: Transport information**

# Land transport (ADR/RID)

14.1. UN number or ID number: UN 1266

14.2. UN proper shipping name: PERFUMERY PRODUCTS

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1

Special Provisions:163 640DLimited quantity:5 LExcepted quantity:E2

Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1266

14.2. UN proper shipping name: Perfumery products

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1

Special Provisions: 163 640D Limited quantity: 5 L Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1266

14.2. UN proper shipping name: PERFUMERY PRODUCTS

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions: 163
Limited quantity: 5 L
Excepted quantity: E2
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1266

14.2. UN proper shipping name: PERFUMERY PRODUCTS

14.3. Transport hazard class(es):

according to UK REACH Regulation

# **Better Feet Prep & Finish**

Revision date: 22.05.2024 Product code: 603 Page 14 of 15

14.4. Packing group:
Hazard label:
3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A3 A72

1 L

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

Danger releasing substance: n-Propanole

#### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice. To avoid risks to man and the environment, comply with the instructions for use.

# Other applicable information

Hazchem code: •3YE

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial 99,803 % (808,404 g/l)

emissions:

Directive 2004/42/EC on VOC in 99,803 % (808,404 g/l)

paints and varnishes:

Subcategory according to Directive

2004/42/EC:

Preparatory and cleaning - Preparatory, VOC limit value: 850 g/l

Information according to Directive

2012/18/EU (SEVESO III):

P5c FLAMMABLE LIQUIDS

### **Additional information**

Other labelling like: Kosmetikverordnung

#### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

# **SECTION 16: Other information**

# Changes

This data sheet contains changes from the previous version in section(s): 2,11,14.

according to UK REACH Regulation

# **Better Feet Prep & Finish**

Revision date: 22.05.2024 Product code: 603 Page 15 of 15

#### Abbreviations and acronyms

Flam. Liq: Flammable liquids Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

# Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Dam. 1; H318	Calculation method
STOT SE 3; H336	Calculation method

# Re

III Liq. L, I ILLO	on basic of tool data
Dam. 1; H318	Calculation method
OT SE 3; H336	Calculation method
elevant H and EUH statements (number and full text)	
H225 Highly	flammable liquid and vapour.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Causes skin irritation.

**EUH066** Repeated exposure may cause skin dryness or cracking.

**EUH208** Contains citral. May produce an allergic reaction.

#### **Further Information**

H315

All data refer to the product upon delivery

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. In case of emergency call CHEMTREC 1-800-424-9300.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)